



# Black stripping pad

## PRODUCT SPECIFICATIONS

### 1.0 Description

The Black Stripping Pad is constructed of polyester fibers in an open texture non-woven fabrication. Abrasive particles are distributed throughout the pad and adhered to the nonwoven construction with a sturdy adhesive.

### 2.0 Properties

Property	Value
Thickness (nominal)	0.94 in 24 mm
Weight (16" Pad)	0.47 lb 212 grams
Fiber Type	Polyester
Fiber Weight	14 oz/yd <sup>2</sup> 475 g/m <sup>2</sup>
Average Mineral Weight (16" Pad)	0.18 lb 81.0 grams
Binder System	Cross-linkable water based
Binder Application	Spray/Dip
Abrasive Application	Spray/Dip
Abrasive	Yes
Color	Black
Pack	5 per case

*Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact Americo with any questions or concerns.*

Americo Manufacturing Company, Inc.

1-800-849-6287  
www.americomfg.com

© 2009

Rev. 1/15/2009  
Black Stripping Pad Product Specifications

### 3.0 Use

Use with water based floor stripping solution to remove worn and soiled floor finishes or sealers. May also used to clean heavily soiled hard surface floors, such as concrete, when used with proper cleaning solutions. For use on standard electric floor machines or automatic scrubbers. Ideal for use on machines speeds up to 350 rpm.

### 4.0 Construction

The Black Stripping Pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides.

### 5.0 Labeling

Labeling is to clearly identify product, size, and quantity. Americo brand or private label is available for this product.

### 6.0 "Green" Initiative

- Polyester fiber used in our pads come from 100% post consumer and industrial recycled waste product.
- Water Based Latex Resins are used in the manufacturing process. No phenol-formaldehyde resins are used in our binding process.
- Shipping cartons contain at least 45% recycled material.
- Plant is operating under EPA approved Clean Air Permit.
- In-house water treatment has reduced our waste water flow by 83%.

### 7.0 Directions for Use

Dust mop or sweep floors prior to stripping. Use pad until soil and finish are removed from floor. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

### 8.0 Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

### 9.0 Sizes

Disc Size (Diameter) (O.D. ± 0.06 inch)	Center Hole
10 inch	3.25 inch
11 inch	3.25 inch
12 inch	3.25 inch
13 inch	3.25 inch
14 inch	3.25 inch
15 inch	3.25 inch
16 inch	3.25 inch
17 inch	3.25 inch
18 inch	3.25 inch
19 inch	3.25 inch
20 inch	3.25 inch
21 inch	3.25 inch
22 inch	3.25 inch
23 inch	3.25 inch
24 inch	3.25 inch

#### Rectangular Size

12 inch x 18 inch  
14 inch x 20 inch  
14 inch x 28 inch  
14 inch x 32 inch

*Additional sizes available.*

*Check for availability on additional center hole dimensions.*